

## Maximum Permissible Exposure

Scan~Link Technologies Inc.

FCC ID: YUU-SLAU270NB

IC: 9283A-SLAU270NB

### Purpose

The purpose of this test is to ensure that the RF energy intentionally transmitted, in terms of power density emitted from the EUT at a stated operating distance does not exceed the limits listed below as defined in the applicable test standard, as calculated based upon readings obtained during testing. This helps protect human exposure to excessive RF fields.

### Limit(s) and Method

The limits, as defined in FCC 1.1310 Table 1 (B), Limits for General Population/Uncontrolled Exposure, was applied. The limit for the frequency range of 1.5 GHz to 100 GHz is 1 mW/cm<sup>2</sup>.

Therefore, the limits for this device are as follows:

MPE Limits	
Frequency	Limit
2.4 – 2.4835 GHz	1.0 mW/cm <sup>2</sup>

The distance used for calculations was 20cm, as this is the minimum distance a user will be from the EUT during normal operation.

Prediction methods from OET Bulletin 65, Edition 97-01 are applied.

### Results

The EUT passed the requirements. The worst case calculated power density is under limits, and meets the MPE test exclusion requirement.

### Calculations for 15.247 device

$$P_d = (\text{EIRP}) / (4 * \pi * R^2)$$

Where:

$P_d$  = Power density

EIRP = Equivalent Isotropic Radiated Power = 19.3 dBm = 85.1 mW

R = 20cm

$$P_d = (85.1 \text{ mW}) / (4 * \pi * 20^2 \text{ cm}^2)$$

$$P_d = 0.01693 \text{ mW/cm}^2$$

$$P_d = 0.01693 \text{ mW/cm}^2 < 1.0 \text{ mW/cm}^2$$

MPE test exclusion applies